



Technische informatie

Motorgegevens RM 50 Hz

pomptype	asvermogen			toerental [opm]			motorrendement			cos phi			koppel			start faktor		J [kgm ²] pomp
	100%	75%	50%	100%	75%	50%	100%	75%	50%	100%	75%	50%	100%	75%	50%	stroom	koppel	
	<i>stroom 220V [A]</i>			<i>stroom 380V [A]</i>			<i>stroom 400V [A]</i>			<i>stroom 415V [A]</i>								
	100%	75%	50%	100%	75%	50%	100%	75%	50%	100%	75%	50%	100%	75%	50%			
RM21DC	1.5 6.6	1.1 5.5	0.8 4.5	1420 3.8	1440 3.2	1455 2.6	71 3.6	69 3.0	65 2.4	0.84 3.5	0.78 2.9	0.68 2.4	10.1	7.5	4.9	4.8	2.0	0.0080
RM21DC-N	1.5 6.6	1.1 5.5	0.8 4.5	1420 3.8	1440 3.2	1455 2.6	71 3.6	69 3.0	65 2.4	0.84 3.5	0.78 2.9	0.68 2.4	10.1	7.5	4.9	4.8	2.0	0.0080
RM21DD	2.2 9.1	1.7 7.2	1.1 5.4	1375 5.3	1415 4.2	1440 3.1	71 5.0	71 3.9	69 3.0	0.89 4.8	0.85 3.8	0.78 2.8	15.3	11.1	7.3	3.4	1.3	0.0080
RM21DG	3.5 14.0	2.6 11.0	1.8 8.9	1385 8.1	1420 6.4	1450 5.2	78 7.7	81 6.1	79 4.9	0.84 7.4	0.77 5.9	0.65 4.7	24.1	17.7	11.5	4.3	1.8	0.0080
RM21DG-L	3.5 14.0	2.6 11.0	1.8 8.9	1385 8.1	1420 6.4	1450 5.2	78 7.7	81 6.1	79 4.9	0.84 7.4	0.77 5.9	0.65 4.7	24.1	17.7	11.5	4.3	1.8	0.0080
RM21DG-N	3.5 14.0	2.6 11.0	1.8 8.9	1385 8.1	1420 6.4	1450 5.2	78 7.7	81 6.1	79 4.9	0.84 7.4	0.77 5.9	0.65 4.7	24.1	17.7	11.5	4.3	1.8	0.0080
RM40DJ	5 20.3	3.8 16.4	2.5 13.4	1420 11.7	1445 9.5	1470 7.7	79 11.1	79 9.0	78 7.3	0.82 10.7	0.76 8.7	0.63 7.1	33.6	24.8	16.2	5.0	1.9	
RM40DL	6 23.8	4.5 18.5	3.0 14.8	1395 13.8	1430 10.7	1460 8.6	78 13.1	80 10.1	78 8.2	0.85 12.6	0.80 9.8	0.68 7.9	41.1	30.0	19.6	4.2	1.5	
RM40DO	7.5 27.6	5.6 21.7	3.8 16.8	1390 16.0	1430 12.6	1460 9.7	81 15.2	81 11.9	79 9.3	0.88 14.6	0.84 11.5	0.74 8.9	51.5	37.6	24.5	6.1	1.8	
RM60LF	22 83.8	16.5 65.3	11.0 51.6	1430 48.5	1450 37.8	1470 29.9	84 46.1	85 35.9	86 28.4	0.82 44.4	0.78 34.6	0.65 27.4	146.	108.	71.5	5.7	1.6	0.1900