



Technische informatie

Nullastdata dompelmotoren 50Hz

Motor type	Nullastvermogen		Nullast stroom [A]					
	[kW]	cos phi	220V	230V	380V	400V	415V	500V
BB	0.3	0.33	2.7	2.5	1.3	1.5	1.8	1.2
BD	0.4	0.31	3.4	3.6	1.7	1.9	2.5	1.5
BE	0.4	0.31	3.4	3.6	1.7	1.9	2.5	1.5
BH	0.7	0.28	6.0	5.7	3.5	3.3	3.2	2.6
BJ	0.8	0.29	7.3	7.0	4.2	4.0	3.8	3.2
BR	0.9	0.24	12.2	11.6	5.7	6.7	8.9	5.3
BZ	0.9	0.24	10.4	9.9	5.1	5.7	6.7	4.6
DA	0.2	0.25	2.1	2.0	1.2	1.1	1.1	0.9
DC	0.3	0.25	3.1	3.0	1.5	1.7	2.0	1.4
DD	0.3	0.25	3.1	3.0	1.5	1.7	2.0	1.4
DG	0.5	0.17	7.6	7.3	4.4	4.2	4.0	3.3
DG-E/C	0.6	0.14	10.9	10.4	6.3	6.0	5.8	4.8
DJ	0.6	0.14	10.9	10.4	6.3	6.0	5.8	4.8
DL	0.6	0.14	10.9	10.4	6.3	6.0	5.8	4.8
DO	0.8	0.14	11.2	10.7	6.5	6.2	6.0	4.9
DU	0.8	0.14	14.7	14.0	8.5	8.1	7.8	6.5
DZ	0.8	0.11	19.5	18.7	11.3	10.7	10.3	8.6
FE	0.3	0.16	5.0	4.8	2.9	2.8	2.7	2.2
FH	0.9	0.21	11.1	10.6	6.4	6.1	5.9	4.9
FR	0.9	0.18	13.0	12.4	7.5	7.2	6.9	5.7
FZ	1.3	0.16	21.7	20.8	12.6	11.9	11.5	9.6
JE	1.8	0.20	23.5	22.4	13.6	12.9	12.5	10.3
JG	2.9	0.28	19.0	18.2	11.0	10.5	10.1	8.4
JL	4.0	0.37	28.3	27.1	16.4	15.6	15.0	12.5
LD	1.2	0.10	31.1	29.7	18.0	17.1	16.5	13.7
LF	1.0	0.11	23.8	22.8	13.6	13.0	12.6	10.5
LI	1.6	0.09	45.4	43.4	26.3	25.0	24.1	20.0
LL	3.0	0.13	52.2	59.4	36.0	34.2	33.0	27.4

Note: een afwijking van 10% is acceptabel